

FIG. 1




FIG. 2




FIG. 5

SC-03-01

3/28




FIG. 3a




FIG. 3b

SC-03-01

4/28




FIG. 3c




FIG. 3d

SC-03-01

5/28




FIG. 4a




FIG. 4b

SC-03-01

6/28

Cone No.: 1; Bit Name: dsgn₂973₁; Bit RPM=60; Cone RPM=98.3511




FIG. 6

SC-03-01

7/28




FIG. 7a




FIG. 7b

SC-03-01

8/28




FIG. 8a




FIG. 8b

ERA22_V Cone No.1




FIG. 9a

SC-03-01

10/28

ERA22_V Cone No.2




FIG. 9b

ERA22_V Cone No.3




FIG. 9c

SC-03-01

11/28




FIG. 10





FIG. 12

SC-03-01

12/28




FIG. 13




FIG. 14

SC-03-01

13/28

Cone No.: 1; Row No.: 2; Bit Name: dsgn₂973₁; Offset: 0




FIG. 15a

Cone No.: 1; Row No.: 2; Bit Name: dsgn₂590₅; Offset: 0




FIG. 15b

SC-03-01

14/28

Cone No.: 1; Row No.: 2; Bit Name: dsgn₂782₂; Offset: 4




FIG. 15c

Cone No.: 1; Row No.: 2; Bit Name: dsgn₃044₃; Offset: 5




FIG. 15d

SC-03-01

15/28





FIG. 16a

SC-03-01

16/28




FIG. 16b

SC-03-01

17/28




FIG. 16c

SC-03-01

18/28





FIG. 16d




FIG. 17

SC-03-01

20/28




FIG. 18a

Energy Balanced Condition of Roller Cone Bit

	Cone 1	Cone 2	Cone 3	Diff (%)	DsgStd (%)
Rock Volume:	38.092	31.024	30.884	7.2	5
Weight on Cone:	38.344	31.3059	30.3501	7.9	5
Bearing Force:	38.888	27.7698	33.3422	11.1	5
Bearing Moment	38.1579	32.3489	29.4932	8.6	5

FIG. 18b

SC-03-01

21/28

The minimal distance between teeth surface is 0.041317 inch





FIG. 19a



Uncut bridges on bottom hole

FIG. 19b

SC-03-01

22/28




FIG. 19c




FIG. 20a

SC-03-01

23/28




FIG. 20b




FIG. 20c




FIG. 21a

Energy Balanced Condition of Roller Cone Bit

	Cone 1	Cone 2	Cone 3	Diff (%)	DsgStd (%)
Rock Volume:	33.0838	34.2063	32.7099	1.4	5
Weight on Cone:	32.784	34.4663	32.7497	1.7	5
Bearing Force:	35.5153	30.4993	33.9854	5	5
Bearing Moment	30.7544	35.6482	33.5974	4.8	5

FIG. 21b




FIG. 22a

Row No.	No. 1	No. 2	No. 3
Cone 1	16	-25	0
Cone 2	32	-38	0
Cone 3	36	-34	0

FIG. 22b




FIG. 23a

SC-03-01

27/28




FIG. 23b

SC-03-01

28/28




FIG. 23c